

# BF BATTEN

## LED SURFACE BATTEN FITTING

A traditionally styled surface batten fitting, available in a wide range of outputs and sizes. Easy to install with emergency options



### Features

- Traditionally styled batten
- Covers BESA boxes, ideal for retro fit
- 1500mm twin fitting
- Opal diffuser
- Suitable for corridors and large spaces



### Specification

| Code     | Description           | Lumen Output | Emergency Lumen Output | Wattage | Efficacy |
|----------|-----------------------|--------------|------------------------|---------|----------|
| BF550W-1 | BF Batten 1500mm Twin | 4500 lm      |                        | 46W     |          |

### Product Information

|                           |               |
|---------------------------|---------------|
| Guarantee                 | 5 Years       |
| Colour Appearance (CCT)   | 4100K         |
| IP Rating                 | IP40          |
| IK Rating                 | IK03          |
| Voltage                   | 230V          |
| Material (Body/Housing)   | Steel         |
| Material (Diffuser/Cover) | Polycarbonate |
| Colour Rendition (CRI)    | Ra > 80       |

|                     |                     |
|---------------------|---------------------|
| Colour Finish       | White               |
| LED Life Expectancy | L70B50 50,000 Hours |
| Power Factor        | 0.95                |
| Frequency           | 50/60Hz             |
| Driver Type         | Fixed Output        |
| Approval            | UKCA & CE           |
| Electrical Class    | Class I             |
| Working Temperature | -15°C to 45°C       |

# BF BATTEN

## LED SURFACE BATTEN FITTING

### Packaging Information

|                         |                             |
|-------------------------|-----------------------------|
| Dimensions (mm)         | L: 1530 x W: 109 x D: 82 mm |
| Product Net Weight (kg) | 2.93 kg                     |
| Barcode                 | 5055807617949               |
| Box Dimensions (mm)     | L: 1536 x W: 114 x D: 85 mm |
| Box Gross Weight (kg)   | 2.75 kg                     |

|                                |                              |
|--------------------------------|------------------------------|
| Units/Outer Carton             | 4                            |
| Outer Carton Barcode           | 25055807617943               |
| Outer Carton Dimensions (mm)   | L: 1550 x W: 240 x D: 190 mm |
| Outer Carton Gross Weight (kg) | 12.0 kg                      |

