

DBR

DIE-CAST IP65 BULKHEAD

The timeless classic design of DBR bulkheads make them suitable for virtually any general outdoor area lighting application. Available as a full diffuser or stylish eyelid version, both can be specified with integral emergency and photocell as options.



Features

- Attractive, classic design with full or eyelid diffuser
- IP65 & IK10 rated for robust outdoor applications
- Integral emergency options available
- Photocell options for dusk to dawn operation



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
DBRE18PC	18W DBR Eyelid Bulkhead with Photocell	1400 lm		18W	78 lm/W

Product Information

Guarantee	5 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	4000K
IP Rating	IP65
IK Rating	IK10
Voltage	220-240V
Material (Body/Housing)	Die-Cast Aluminium
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra > 80

Colour Finish	Black
LED Life Expectancy	L70B50 50,000 Hours
Power Factor	>0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-20°C to 45°C



DBR

DIE-CAST IP65 BULKHEAD

Packaging Information

Dimensions (mm)	Ø: 275 x D: 85 mm
Product Net Weight (kg)	1.45 kg
Barcode	5055807617079
Box Dimensions (mm)	L: 280 x W: 280 x D: 90 mm
Box Gross Weight (kg)	1.6 kg

Units/Outer Carton	10
Outer Carton Barcode	15055807617076
Outer Carton Dimensions (mm)	L: 480 x W: 300 x D: 590 mm
Outer Carton Gross Weight (kg)	16.9 kg

