

# FLAC SITE SLIMLINE FLOODS

## 110V SLIMLINE FLOODLIGHT

FLAC site floodlights are lightweight, yet robust, thanks to die-cast aluminium construction. Using cost effective driver-on-board technology, the range offers high efficacy and value for money.



### Features

- Ultra slim, lightweight design
- Bracket allows 360° adjustment
- High efficacy 95 lm/W
- Built in surge protection
- Pre-wired with 1m cable



### Specification

| Code    | Description              | Lumen Output | Emergency Lumen Output | Wattage | Efficacy |
|---------|--------------------------|--------------|------------------------|---------|----------|
| FLAC50Y | FLAC Site Floodlight 50W | 4750 lm      |                        | 50W     | 95 lm/W  |

### Product Information

|                           |                    |
|---------------------------|--------------------|
| Guarantee                 | 2 Years            |
| Colour Appearance (CCT)   | 6500K              |
| IP Rating                 | IP65               |
| IK Rating                 | IK07               |
| Voltage                   | 110V               |
| Material (Body/Housing)   | Die-Cast Aluminium |
| Material (Diffuser/Cover) | Tempered Glass     |
| Colour Rendition (CRI)    | Ra 80              |

|                     |                     |
|---------------------|---------------------|
| Colour Finish       | Yellow              |
| LED Life Expectancy | L70B50 30,000 Hours |
| Power Factor        | 0.9                 |
| Frequency           | 50Hz                |
| Driver Type         | Fixed Output        |
| Approval            | UKCA & CE           |
| Electrical Class    | Class I             |
| Working Temperature | -20°C to 45°C       |



# FLAC SITE SLIMLINE FLOODS

## 110V SLIMLINE FLOODLIGHT

### Packaging Information

|                         |                            |
|-------------------------|----------------------------|
| Dimensions (mm)         | L: 205 x W: 165 x D: 33 mm |
| Product Net Weight (kg) | 0.68 kg                    |
| Barcode                 | 5055807620727              |
| Box Dimensions (mm)     | L: 230 x W: 178 x D: 40 mm |
| Box Gross Weight (kg)   | 0.76 kg                    |

|                                |                             |
|--------------------------------|-----------------------------|
| Units/Outer Carton             | 20                          |
| Outer Carton Barcode           | 15055807620724              |
| Outer Carton Dimensions (mm)   | L: 420 x W: 370 x D: 245 mm |
| Outer Carton Gross Weight (kg) | 14.2 kg                     |

