

FLSMD SITE FLOODS

MULTI-VOLTAGE

FLSMD is a range of tough and robust floodlights designed for site applications. Featuring a multi-voltage supply driver, FLSMD can be used in virtually any project.



Features

- Symmetrical 120° distribution
- Convenient multi-voltage drivers
- Tough die-cast construction
- Pre-wired with 1m cable



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
FLSMD150Y-1	FLSMD Site Floodlight 150W	12,000 lm		150W	80 lm/W

Product Information

Guarantee	3 Years
Colour Appearance (CCT)	6500K
IP Rating	IP65
IK Rating	IK07
Voltage	110V
Material (Body/Housing)	Die-Cast Aluminium
Material (Diffuser/Cover)	Tempered Glass
Colour Rendition (CRI)	Ra 70

Colour Finish	Yellow
LED Life Expectancy	L70B50 35,000 Hours
Power Factor	0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA & CE
Electrical Class	Class I
Working Temperature	-20°C to 40°C



FLSMD SITE FLOODS

MULTI-VOLTAGE

Packaging Information

Dimensions (mm)	L: 365 x W: 370 x D: 94 mm
Product Net Weight (kg)	4.8 kg
Barcode	5055807620123
Box Dimensions (mm)	L: 375 x W: 375 x D: 125 mm
Box Gross Weight (kg)	5 kg

Units/Outer Carton	2
Outer Carton Barcode	15055807620120
Outer Carton Dimensions (mm)	L: 395 x W: 395 x D: 265 mm
Outer Carton Gross Weight (kg)	10.22 kg

