

GLOBE LIGHT

360° WORKSPACE LIGHTING

For ultimate flexibility, our Globe Light is the number one choice. Featuring 360° light distribution, the unit can be free standing, tripod mounted or suspended using the built-in hook. An emergency version offers complete peace of mind.



Features

- Lightweight and portable
- Efficient 360° light distribution
- Emergency option, switchable to prevent discharge during storage
- Built-in hook for suspension mounting
- Adjustable tripod available to order separately



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
GLS30YPW	Globe Light c/w 5m cable +plug	2600 lm		30W	86 lm/W

Product Information

Guarantee	2 Years
Colour Appearance (CCT)	6500K
IP Rating	IP44
IK Rating	IK07
Voltage	110V
Material (Body/Housing)	ABS
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra > 80

Colour Finish	Yellow
LED Life Expectancy	L70B50 35,000 Hours
Power Factor	0.9
Frequency	50Hz
Driver Type	Fixed Output
Approval	UKCA & CE
Electrical Class	Class I
Working Temperature	-20°C to 40°C

GLOBE LIGHT

360° WORKSPACE LIGHTING

Packaging Information

Dimensions (mm)	Ø: 190 x L: 252 mm
Product Net Weight (kg)	1.86 kg
Barcode	5055807620451
Box Dimensions (mm)	L: 240 x W: 200 x D: 260 mm
Box Gross Weight (kg)	2.3 kg

Units/Outer Carton	4
Outer Carton Barcode	15055807620458
Outer Carton Dimensions (mm)	L: 420 x W: 255 x D: 545 mm
Outer Carton Gross Weight (kg)	10.5 kg

