

GTC

MULTI-FIT LED GEAR TRAY

High quality LED Gear Trays, suitable for use with POLO X and Robust empty bodies and also with a wide range of legacy bulkhead housings (subject to fixing centres and internal volume).











Features

- Improved efficacy of up to 138 lm/W
- Emergency & microwave sensor options available
- Fitted with integral LED driver
- Designed for POLO X and Robust empty body circular bulkhead fittings
- Suitable for a wide range of proprietary bulkheads including 2D lamp, subject to fixing centres and thermal considerations



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
GTC13/MSCF- 35	Circular Gear Tray 13W 3500K c/w M/W Sensor & CF	1800 lm		13W	138 lm/W

Product Information

Guarantee	5 Years	
On-Site Warranty	2 Years	
Colour Appearance (CCT)	3500K	
Voltage	230V	
Material (Body/Housing)	Phenolic Resin	
Colour Rendition (CRI)	> Ra 80	
Colour Finish	White	

LED Life Expectancy	L80B50 40,000 Hours	
Power Factor	>0.85	
Frequency	50Hz	
Driver Type	Fixed Output	
Approval	UKCA CE	
Electrical Class	Class II	
Working Temperature	-20°C to 40°C	

Tel: 0114 279 8999 | Email: sales@redarrowelectrical.co.uk | redarrowelectrical.co.uk




GTC


MULTI-FIT LED GEAR TRAY


Packaging Information

Dimensions (mm)	Ø: 245 X D: 46mm	
Product Net Weight (kg)	0.22 kg	
Barcode	5055807622035	
Box Dimensions (mm)	L: 265 x W: 250 x D: 55 mm	
Box Gross Weight (kg)	0.32 kg	

Units/Outer Carton	10	
Outer Carton Barcode	15055807622032	
Outer Carton Dimensions (mm)	L: 30.5 x W: 27.5 x D: 52 mm	
Outer Carton Gross Weight (kg)	4.2 kg	







Tel: 0114 279 8999 | Email: sales@redarrowelectrical.co.uk | redarrowelectrical.co.uk