

# 502B EXIT SIGN

## RECESSED BLADE STYLE EXIT SIGN

Designed for recessed applications, particularly retrofit, the 502B exit sign features a high quality legend blade. The housing has fully adjustable brackets suitable for use in different ceiling thicknesses.



### Features

- Recessed mounting with fully adjustable brackets, fixed from below
- Supplied with high quality Up Arrow Legend
- Choice of other legends to order

### Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
LFACLED502B	502B Recessed Blade Exit Sign M/NM	61		3.3W	

### Product Information

Guarantee	1 Year
Emergency Battery Guarantee	1 Year
Colour Appearance (CCT)	6000K
IP Rating	IP20
Emergency Battery Type	Ni-Cd
Voltage	230V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra > 70

Colour Finish	White
LED Life Expectancy	L70B50 50,000 Hours
Frequency	50Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	0°C to 40°C
EM Working Temperature	0°C to 40°C



# 502B EXIT SIGN

## RECESSED BLADE STYLE EXIT SIGN

### Packaging Information

Dimensions (mm)	L: 410 x W: 135 x D: 260mm
Product Net Weight (kg)	2.15 kg
Barcode	5055807607902
Box Dimensions (mm)	L: 425 x W: 125 x D: 85 mm
Box Gross Weight (kg)	2.35 kg

Units/Outer Carton	6
Outer Carton Dimensions (mm)	L: 435 x W: 395 x D: 390 mm
Outer Carton Gross Weight (kg)	14.95 kg

