

LINEAR

SLIMLINE SURFACE LUMINAIRES

The Linear range of surface luminaires has a stylish, shallow profile, suitable for many applications where a discreet solution is required. Linear can also be suspended using an adjustable steel wire rope kit.



Features

- Ultra shallow profile and stylish aesthetics
- Choice of sizes and colour temperature
- Stainless Steel Rope Suspension Kit available to order separately
- IK08 - Suitable for industrial use



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
LINA220W-60	LED Linear Fitting 600mm	1750 lm		20W	87 lm/W

Product Information

Guarantee	3 Years
On-Site Warranty	1 Year
Colour Appearance (CCT)	6000K
IP Rating	IP40
IK Rating	IK08
Voltage	100-240V
Material (Body/Housing)	Aluminium
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra > 80

Colour Finish	Satin Silver/White
LED Life Expectancy	L70B50 35,000 Hours
Power Factor	>0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-20°C to 40°C

LINEAR

SLIMLINE SURFACE LUMINAIRES

Packaging Information

Dimensions (mm)	L: 580 x W: 80 x D: 36 mm
Product Net Weight (kg)	0.59 kg
Barcode	5055807618175
Box Dimensions (mm)	L: 610 x W: 84 x D: 38 mm
Box Gross Weight (kg)	0.68 kg

Units/Outer Carton	20
Outer Carton Barcode	15055807618172
Outer Carton Dimensions (mm)	L: 630 x W: 360 x D: 215 mm
Outer Carton Gross Weight (kg)	14 kg

