

LINEAR

SLIMLINE SURFACE LUMINAIRES

The Linear range of surface luminaires has a stylish, shallow profile, suitable for many applications where a discreet solution is required. Linear can also be suspended using an adjustable steel wire rope kit.



Features

- Ultra shallow profile and stylish aesthetics
- Choice of sizes and colour temperature
- Stainless Steel Rope Suspension Kit available to order separately
- IK08 - Suitable for industrial use

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
LINA560W-60	LED Linear Fitting 1500mm	5300 lm		60W	88 lm/W

Product Information

Guarantee	3 Years
On-Site Warranty	1 Year
Colour Appearance (CCT)	6000K
IP Rating	IP40
IK Rating	IK08
Voltage	100-240V
Material (Body/Housing)	Aluminium
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra > 80

Colour Finish	Satin Silver/White
LED Life Expectancy	L70B50 35,000 Hours
Power Factor	>0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-20°C to 40°C

LINEAR

SLIMLINE SURFACE LUMINAIRES

Packaging Information

Dimensions (mm)	L: 1480 x W: 80 x D: 36 mm
Product Net Weight (kg)	1.08 kg
Barcode	5055807618212
Box Dimensions (mm)	L: 1510 x W: 84 x D: 38 mm
Box Gross Weight (kg)	1.3 kg

Units/Outer Carton	10
Outer Carton Barcode	15055807618219
Outer Carton Dimensions (mm)	L: 1530 x W: 215 x D: 185 mm
Outer Carton Gross Weight (kg)	14 kg

