SPECIFICATION SHEET



5-IN1 EXIT SIGN MULTI-POSITIONAL EXIT SIGN

Our 5 in 1 LED Emergency Exit Sign is incredibly versatile and can be mounted in 5 different ways, without any additional accessories. Can be configured for maintained or non-maintained operation.



Features

- Ceiling, wall and 90° flag mounting
- Suspended and recessed mounting kits included
- Choice of legend (supplied separately)
- Latest LiFeP04 battery technology



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
MPESPW	5 in 1 LED Exit Sign M/NM	60		1W/2W	

Product Information

Guarantee	2 Years	
Emergency Battery Guarantee	1 Year	
Colour Appearance (CCT)	6000K	
IP Rating	IP20	
IK Rating	IK02	
Emergency Battery Type	LiFePO4	
Voltage	230V	
Material (Body/Housing)	Polycarbonate	
Material (Diffuser/Cover)	Acrylic	

Colour Rendition (CRI)	Ra > 70	
Colour Finish	White	
LED Life Expectancy	L70B50 40,000 Hours	
Frequency	50Hz	
Driver Type	Fixed Output	
Approval	UKCA CE	
Electrical Class	Class II	
Working Temperature	0°C to 40°C	
EM Working Temperature	0°C to 40°C	

Tel: 0114 279 8999

Email: sales@redarrowelectrical.co.uk

redarrowelectrical.co.uk

Red Arrow Electrical Ltd, Cortonwood Drive, Brampton, Barnsley, S73 0UF

This document is uncontrolled if printed, all information is subject to change. Generated on 06/05/24


RED ARROW

5-IN1 EXIT SIGN MULTI-POSITIONAL EXIT SIGN

Packaging Information

Dimensions (mm)	L: 315 x W: 69 x D: 50 mm	
Product Net Weight (kg)	0.32 kg	
Barcode	5055807620574	
Box Dimensions (mm)	L: 340 x W: 70 x D: 65 mm	
Box Gross Weight (kg)	0.4 kg	

Units/Outer Carton	20	
Outer Carton Barcode	15055807620571	
Outer Carton Dimensions (mm)	L: 380 x W: 360 x D: 280 mm	
Outer Carton Gross Weight (kg)	8.55 kg	



Tel: 0114 279 8999 Email: sales@redarrowelectrical.co.uk redarrowelectrical.co.uk

Red Arrow Electrical Ltd, Cortonwood Drive, Brampton, Barnsley, S73 0UF

This document is uncontrolled if printed, all information is subject to change. Generated on 06/05/24