

T8 TUBES

18W 4' 4000K LED T8 TUBE

Ideal for a wide variety of applications and are particularly suitable for use with our Weatherguard range of non-corrosive fittings. An ideal replacement for T8 fluorescent tubes.



Features

- Non-dimmable
- Wired live and neutral to one end
- Suitable for Weatherguard WG range (Pg 46)



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
T8LED418-40	18W 4' 4000K LED T8 Tube	1700 lm		18W	94 lm/W

Product Information

Guarantee	3 Years
Colour Appearance (CCT)	4000K
IP Rating	IP20
Voltage	90 - 265V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate

Colour Rendition (CRI)	Ra 80
LED Life Expectancy	L70B50 25,000 Hours
Power Factor	>0.9
Driver Type	Fixed Output
Approval	UKCA CE
Working Temperature	-20°C to 40°C

T8 TUBES

18W 4' 4000K LED T8 TUBE

Packaging Information

Dimensions (mm)	L: 1213 x Ø: 28 mm
Product Net Weight (kg)	0.193 kg
Barcode	5055807615860
Box Dimensions (mm)	L: 1233 x Ø: 38 mm
Box Gross Weight (kg)	0.307 kg

Units/Outer Carton	25
Outer Carton Barcode	15055807615867
Outer Carton Dimensions (mm)	L: 1265 x W: 207 x D: 215 mm
Outer Carton Gross Weight (kg)	8.3 kg

