



WEATHERGUARD PLUS

NON-CORROSIVE FITTINGS

Weatherguard Plus takes IP65 corrosion resistant luminaires to the next level. The range features high efficiency up to 120 lm/W LEDs and stainless steel clips. The driver & LEDs are replaceable at the end of life, making a more environmentally friendly fitting.



Features

- Unique plug-in replaceable LED strips
- High efficacy - upto 120lm/w.
- Stainless steel clips included as standard
- Strong corrosion resistant IP65 housing
- Integral microwave sensors available



Specification

| Code | Description | Lumen Output | Emergency Lumen Output | Wattage | Efficacy |
|--------|-------------------------|--------------|------------------------|---------|----------|
| WGP212 | Weatherguard Plus 600mm | 1350 lm | | 12W | 113 lm/W |

Product Information

| | |
|---------------------------|---------------|
| Guarantee | 7 Years |
| On-Site Warranty | 2 Years |
| Colour Appearance (CCT) | 4000K |
| IP Rating | IP65 |
| IK Rating | IK07 |
| Voltage | 230V |
| Material (Body/Housing) | Polycarbonate |
| Material (Diffuser/Cover) | Polycarbonate |
| Colour Rendition (CRI) | Ra > 80 |

| | |
|---------------------|---------------------|
| Colour Finish | Grey |
| LED Life Expectancy | L70B50 30,000 Hours |
| Power Factor | 0.9 |
| Frequency | 50/60Hz |
| Driver Type | Fixed Output |
| Approval | UKCA CE |
| Electrical Class | Class I |
| Working Temperature | -25°C to 40°C |



WEATHERGUARD PLUS

NON-CORROSIVE FITTINGS

Packaging Information

| | |
|-------------------------|----------------------------|
| Dimensions (mm) | L: 664 x W: 103 x D: 78 mm |
| Product Net Weight (kg) | 0.78 kg |
| Barcode | 5055807621298 |
| Box Dimensions (mm) | L: 100 x W: 82 x D: 75 mm |
| Box Gross Weight (kg) | 0.85 kg |

| | |
|--------------------------------|-----------------------------|
| Units/Outer Carton | 8 |
| Outer Carton Barcode | 25055807621292 |
| Outer Carton Dimensions (mm) | L: 690 x W: 225 x D: 350 mm |
| Outer Carton Gross Weight (kg) | 7.35 kg |

