

WEATHERGUARD PLUS

NON-CORROSIVE FITTINGS

Weatherguard Plus takes IP65 corrosion resistant luminaires to the next level. The range features high efficiency up to 120 lm/W LEDs and stainless steel clips. The driver & LEDs are replaceable at the end of life, making a more environmentally friendly fitting.















Features

- Unique plug-in replaceable LED strips
- High efficacy upto 120lm/w.
- Stainless steel clips included as standard
- Strong corrosion resistant IP65 housing
- Integral microwave sensors available



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
WGP224-E	Weatherguard Plus 600mm with 3HR Emergency	2500 lm	259 lm	24W	104 lm/W

Product Information

Guarantee	7 Years
Emergency Battery Guarantee	5 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	4000K
IP Rating	IP65
IK Rating	IK07
Emergency Battery Type	LiFePO4
Voltage	230V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate

Colour Rendition (CRI)	Ra > 80	
Colour Finish	Grey	
LED Life Expectancy	L70B50 30,000 Hours	
Power Factor	0.9	
Frequency	50/60Hz	
Driver Type	Fixed Output	
Approval	UKCA CE	
Electrical Class	Class I	
Working Temperature	0°C to 40°C	
EM Working Temperature	0°C to 40°C	

Tel: 0114 279 8999 | Email: sales@redarrowelectrical co.uk | redarrowelectrical co.ul



WEATHERGUARD PLUS


NON-CORROSIVE FITTINGS


Packaging Information


Dimensions (mm)	L: 664 x W: 103 x D: 78 mm	
Product Net Weight (kg)	1.08 kg	
Barcode	5055807621311	
Box Dimensions (mm)	L: 100 x W: 105 x D: 80 mm	
Box Gross Weight (kg)	1.15 kg	

Units/Outer Carton	8	
Outer Carton Barcode	15055807621318	
Outer Carton Dimensions (mm)	L: 690 x W: 225 x D: 350 mm	
Outer Carton Gross Weight (kg)	9.9 kg	









Геl: 0114 279 8999

Email: sales@redarrowelectrical.co.uk

redarrowelectrical.co.uk