

WEATHERGUARD SITE WITH FLEX & JB

FLEX & JUNCTION BOX

For fast and efficient installation, Weatherguard Site is also available pre-wired with 1m of cable and junction box. Save time and money on site.



Features

- Pre-wired with 1m cable and junction box
- Fast and easy to install
- High efficacy - 100 lm/W
- Standard & emergency versions available



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
WGS220Y/PC	Weatherguard Site 600mm c/w Flex & Junction Box	2000 lm		20W	100 lm/W

Product Information

Guarantee	3 Years
Colour Appearance (CCT)	4000K
IP Rating	IP65
IK Rating	IK07
Voltage	110V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra > 80

Colour Finish	Yellow
LED Life Expectancy	L70B50 30,000 Hours
Power Factor	0.5
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA & CE
Electrical Class	Class I
Working Temperature	-25°C to 40°C

WEATHERGUARD SITE WITH FLEX & JB

FLEX & JUNCTION BOX

Packaging Information

Dimensions (mm)	L: 664 x W: 103 x D: 78 mm
Product Net Weight (kg)	1.1 kg
Barcode	5055807622721
Box Dimensions (mm)	L: 810 x W: 110 x D: 80 mm
Box Gross Weight (kg)	1.15 kg

Units/Outer Carton	9
Outer Carton Barcode	15055807622728
Outer Carton Dimensions (mm)	L: 825 X W: 340 x D: 250 mm
Outer Carton Gross Weight (kg)	11.5 kg

