

WEATHERGUARD SITE

IP65 NON-CORROSIVE FITTINGS

Weatherguard Site offers the very latest in IP65 non-corrosive site lighting. High efficiency 100 lm/W LEDs and stainless steel clips as standard, plus LEDs and drivers that can easily be replaced at the end of life, for minimum environmental impact.



Features

- Unique, future proof replaceable LED modules
- Durable IP65 & IK07 body and diffuser
- High efficacy - 100 lm/W
- Emergency versions available



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
WGS550Y-E	Weatherguard Site 1500mm c/w 3HR Emergency	5000 lm	450 lm	50W	100 lm/W

Product Information

Guarantee	3 Years
Emergency Battery Guarantee	3 Years
Colour Appearance (CCT)	4000K
IP Rating	IP65
IK Rating	IK07
Emergency Battery Type	LiFePO4
Voltage	110V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra > 80

Colour Finish	Yellow
LED Life Expectancy	L80B50 30,000 Hours
Power Factor	>0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA & CE
Electrical Class	Class I
Working Temperature	0°C to 40°C
EM Working Temperature	0°C to 40°C

WEATHERGUARD SITE

IP65 NON-CORROSIVE FITTINGS

Packaging Information

Dimensions (mm)	L: 1562 x W: 103 x D: 78 mm
Product Net Weight (kg)	2.20 kg
Barcode	5055807621243
Box Dimensions (mm)	L: 1562 x W: 103 x D: 78 mm
Box Gross Weight (kg)	2.25 kg

Units/Outer Carton	6
Outer Carton Barcode	15055807621240
Outer Carton Dimensions (mm)	L: 1590 x W: 255 x D: 225 mm
Outer Carton Gross Weight (kg)	14.4 kg

